

Application No. 10/604,428
Confirmation No. 1427
Attorney Docket No. D9446

CLAIMS LISTING

[c1] - [c3] (Cancelled)

[c4] (Withdrawn) The apparatus of claim 2 wherein said support member is a penetrating fastener.

[c5] - [c8] (Cancelled)

[c9] (New) An apparatus for hanging items comprising:
a body with a recess;
a hanging member with a first end and a second end;
said hanging member rotatably mounted on a rotation axis within said recess;
said hanging member being capable of rotating about said rotation axis between a recessed position and a hanging position;
where at said recessed position said first end and said second end of said hanging member are both located within said recess, with there being a space between said first end and a floor of said recess; and
where at said hanging position said second end of said hanging member extends out of said recess, and said first end is in contact with said recess floor.

[c10] (New) The apparatus of claim 9 wherein said body also contains a channel for a support member.

[c11] (New) The apparatus of claim 10 wherein said support member is a belt.

[c12] (New) The apparatus of claim 9 wherein said rotation axis is a pin.

[c13] (New) The apparatus of claim 9 further comprising a finger extending from said hanging member.

Application No. 10/604,428
Confirmation No. 1427
Attorney Docket No. D9446

[c14] (New) A portable system for hanging items comprising:
a support member;
a body;
said body containing a channel for receiving said support member;
said body further containing a recess;
a hanging member with a first end and a second end;
said hanging member rotatably mounted on a rotation axis within said recess;
said hanging member being capable of rotating about said rotation axis between
a recessed position and a hanging position;
where at said recessed position said first end and said second end of said
hanging member are both located within said recess, with there being a space
between said first end and a floor of said recess; and
where at said hanging position said second end of said hanging member extends
out of said recess, and said first end is in contact with said recess floor.

[c15] (New) A method of hanging an item from an object using the portable
system of claim 14 comprising the steps of; inserting said support member
through said channel; securing said body to an object with said support member;
pressing on said first end so as to rotate said hanging member about said
rotation axis until said first end and said recess floor make contact; and hanging
an item on said second end of said hanging member that extends out of said
recess.